

Entry Line

1 port Device Server

1x RS-232/422/485, 2x 10/100Base-TX

1x 100Base-X (optional)

General

The IP protocol has already left the in-house environment and is going to take all remaining communication areas. Industrial Ethernet already is an established idea, describing the reliable use of Ethernet components in harsh environments.

Because of the large number of these applications the market requires simple and also reliable and cost effective products. With the new Industrial Ethernet Entry Line MICROSENS fulfils these requirements. The products are very compact and include:

- 5 and 8 port Fast Ethernet Switches
- 8 Port Gigabit Ethernet Switch
- Switches with fiber-uplink
- Media Converter for Fast Ethernet and Gigabit Ethernet
- Device Server for the conversion of serial interfaces (RS-232/422/485) to IP.

All new devices distinguish themselves with easy handling (Plug&Play) and do not need extensive configuration. New developments are focusing on increasing the port numbers and further implementation of Gigabit Ethernet.



Fig. 1: 1 port Device Server

This Device Server enables the transmission of old legacy equipment with RS-232/422/485 interface via modern IP based networks. One system consist always out of one Device Server and a software installed on a PC where a virtual COM port is installed.

Features

- RS-232/422/485 to Ethernet (IP)
- Windows Utility for discovery, configuration and monitoring
- Max. data rate up to 460.8 Kbps
- Virtual COM, TCP Server, TCP Client connections

Technical Specifications

Type	RS-232/422/485 Device Server for industrial use
Fiber type	Multimode 62.5/125 ~ 50/125um (optional), Single Mode 9/125um, duplex (optional)
Cable type serial	Twisted Pair cable, SUB-D9 (male)
Cable type Ethernet	Shielded Twisted Pair cable, 100 Ohm, Category 5, RJ-45
Data rate	up to 460.8 Kbps
LED displays	PWR 1 / Ready: 1) Red On: Power is on and booting up. Red Blinking: Indicates an IP conflict, or DHCP or BOOTP server did not respond properly. 2) Green On: Power is on and functioning normally. Green Blinking: Located by Administrator's Location function. PWR 2 / Ready: 1) Red On: Power is on and booting up. Red Blinking: Indicates an IP conflict, or DHCP or BOOTP server did not respond properly. 2) Green On: Power is on and functioning normally. Green Blinking: Located by Administrator's Location function. Eth1 Link / ACT: Orange Blinking: 10 Mbps Ethernet; Green Blinking:100 Mbps Ethernet Eth2 Link / ACT: Orange Blinking:10 Mbps Ethernet; Green Blinking:100 Mbps Ethernet TX / RX: Serial port is receiving data(Orange); Serial port is transmitting data(Green).
Utilities	X-Ware for Windows NT/2000/XP/2003
Management	Web, X-Ware Utilities, SNMP and Telnet
Mounting	35 mm hat rail, according DIN EN 50 022 and wall mount
Power supply	12 - 48 VDC / connections with screw terminals redundant port with DC jack
Dimensions	72 x 32 x 100 mm (w x d x h)
Operating temperature	-10°C to 60°C
Storage temperature	-40°C to 85°C
Rel. humidity	5% to 95% non condensing
EMC	FCC Class A,CE Class A
Safety	UL, cUL,

Safety Notes

WARNING: Infrared radiation as used for data transmission within the fiber optic, although invisible to the human eye, can nevertheless cause damage.

To avoid damage to the eyes:

- never look straight into the output of fiber optic components – danger of blinding!
- cover all unused optical connections with caps.
- commission the transmission link only after completing all connections.

The active laser components used with this product comply with the provisions of **Laser Class 1**.

DANGER: Conductive components of power and telecommunications networks can carry dangerously high voltage.

To avoid electric shock:

- Do not carry out installation or maintenance work during lightning storms.
- All electric installations must be carried out in accordance with local regulations.

Order Information

Art.-No.	Description	Connectors
MS655400	Industrial Ethernet Device Server, Entry Line, 1x RS-232/422/485 to 2x 10/100Base-TX	1x SUB-D9 2x RJ-45
MS655401	Industrial Ethernet Device Server, Entry Line, 1x RS-232/422/485 to 1x 100Base-FX Multimode 1310nm SC	1x SUB-D9 1x SC duplex

Accessories

Art.-No.	Description	Connectors
MS700420	Hat-rail power supply 24 Watt 24 V / 1,0 A, wide range input 85-264 VAC	In: 3-pin Out: 2-pin
MS700421	Hat-rail power supply 60 Watt 24 V / 2,5 A, wide range input 85-264 VAC	In: 3-pin Out: 5-pin
MS700422	Hat-rail power supply 120 Watt 24 V / 5 A, wide range input 85-264 VAC	In: 3-pin Out: 5-pin
MS700434	DC/DC hat-rail power supply 24 Watt 24 V / 1,0 A, wide range input 18-75 V DC	In: 3-pin Out: 2-pin

MICROSENS reserves the right to make any changes without further notice to any product to improve reliability, function or design. MICROSENS does not assume any liability arising out of the application or use of any product. 2007/He

www.microsens.com